

US008955217B2

# (12) United States Patent

Burrows et al.

# (54) METHOD FOR EDGE SEALING BARRIER FILMS

(75) Inventors: **Paul Burrows**, Kennewick, WA (US); **J. Chris Pagano**, Santa Clara, CA (US);

Eric S. Mast, Richland, WA (US); Peter M. Martin, Kennewick, WA (US); Gordon L. Graff, West Richland, WA (US); Mark E. Gross, Pasco, WA (US); Charles C. Bonham, Richland, WA (US); Wendy D. Bennett, Kennewick, WA (US); Michael G. Hall, West

Richland, WA (US)

(73) Assignee: Samsung Display Co., Ltd., Yongin

(KR)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days. (21) Appl. No.: 13/353,635

(22) Filed: Jan. 19, 2012

(65) Prior Publication Data

US 2012/0118855 A1 May 17, 2012

### Related U.S. Application Data

- (60) Division of application No. 11/068,356, filed on Feb. 28, 2005, now abandoned, which is a division of application No. 09/966,163, filed on Sep. 28, 2001, now Pat. No. 6,866,901, which is a continuation-in-part of application No. 09/427,138, filed on Oct. 25, 1999, now Pat. No. 6,522,067.
- (51) Int. Cl. H01L 23/10 (2006.01) H01L 23/00 (2006.01) (Continued)

(Continued)

### (45) **Date of Patent:**

(10) **Patent No.:** 

US 8,955,217 B2

Feb. 17, 2015

#### (58) Field of Classification Search

CPC . H01L 23/562; H01L 23/564; H01L 51/5237; H01M 2/08

See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

2,382,432 A 8/1945 McManus et al. 2,384,500 A 9/1945 Stoll

(Continued)

#### FOREIGN PATENT DOCUMENTS

BE 704297 2/1968 CA 2 353 506 5/2000 (Continued)

OTHER PUBLICATIONS

De Gryse, R., et al., Sputtered Transparent Barrier Layers, 10th International Conference on Vacuum Web Coating (Edited by R. Bakish) aka the 10th Bakish Conference; 1996, pp. 190-198.

(Continued)

Primary Examiner — Livius R Cazan (74) Attorney, Agent, or Firm — Dinsmore & Shohl LLP

#### (57) ABSTRACT

An edge-sealed barrier film composite. The composite includes a substrate and at least one initial barrier stack adjacent to the substrate. The at least one initial barrier stack includes at least one decoupling layer and at least one barrier layer. One of the barrier layers has an area greater than the area of one of the decoupling layers. The decoupling layer is sealed by the first barrier layer within the area of barrier material. An edge-sealed, encapsulated environmentally sensitive device is provided. A method of making the edge-sealed barrier film composite is also provided.

#### 12 Claims, 3 Drawing Sheets

